# Technical Data



# **GEAR AND WIRE ROPE LUBRI CANT** AVY DUTY LUBRICANT



GEAR AND WIRE ROPE LUBRICANT is formulated to provide protection and lubrication for open gears and wire ropes under all operating conditions.

# **APPLICATIONS**

The product penetrates deeply for internal protection of open gears, wire ropes, racks and pinions, crown wheels and cams and driving mechanisms in the Construction, Shipyard, Docks and Marine, Quarrying, Plant Hire, Heavy Engineering, Automotive and Manufacturing

# industries:

Tower Cranes

- Overhead Cranes
  Derrick Cranes

- Mobile Cranes
- Hoists and Winches
  Excavators
- Agricultural Machinery
- Printing Machinery
  Food Machinery
- Textile Machinery
- Paper Making Machinery

Quick to dry, the product adheres strongly to all treated areas and forms a dry, solids-enhanced, non-peeling film which reduces wear and extends the operational life of the equipment. The tough, durable coating resists corrosion, abrasion, dust absorption, water wash and extremes of temperature, making it ideal for external use or for dustladen atmospheres.

Apply a light, even coating from 9" - 12" (25 - 30 cm) and re-apply as necessary. Can be applied to running gear mechanisms if required. On wire ropes, allow 15 minutes for full penetration before use of equipment.

# TECHNICAL DATA

Appearance Black liquid

Odour Hydrocarbon

SG @ 25°C

Pressure @ 25°C 3.5 Bar

Discharge rate 0.76 g/sec

-25°C to +100°C Temperature range

Solubility : Soluble in most organic solvents, insoluble

in water

Recommended solvents : Amberklene FE10 or ME20

Flammability : Classified as extremely flammable under

current EC Regulations

Flashpoint : Not applicable in sealed aerosol

Packaging : 400 ml aerosol (12 per carton).

# **STORAGE**

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

# **HEALTH AND SAFETY**

Health and Safety sheet available separately.

# **TECHNICAL SERVICE**

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

# MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Ltd, Wylds Road, Bridgwater, Somerset, TA6 4DD, UK.

Tel: +44 (0) 1278 727200 Fax: +44 (0) 1278 425644

Web: www.ambersil.com E-mail: sales.uk@crcind.com